

SF-VIK002-S-WIP

Video-intercom kit


IP Technology & WiFi

Includes panel and monitor

MIFARE Reader : Standard PoE

Mobile App with P2P

Surface mounting



Safire

Intercom Kit

IP Interface

Kit consisting of: SF-VI111-IPW-1MF external video intercom panel for surface

2Mpx HD camera board

SF-VIDISP01-7WIP 7" LCD TFT interior monitor

Powered by Standard PoE (IEEE 802.3af)

Monitoring through Safire Control Center-software or mobile app

Specifications

Panel

Brand	Safire
Model	SF-VI111-IPW-1MF
Operating system	LINUX OS
Image sensor	1/3" 2 Megapixel CMOS
Audio	Bidirectional audio with microphone and speaker
Access Control	Door opening with Mifare card 13.65MHz up to 256
Keypad	Mechanical button with LED backlit name-tag
Relay	1 for lock control.
Inputs	Exit button, feedback, door sensor, tamper
Remote access	Web browser, phone app or Safire Control Center-software
Network interface	Ethernet 10/100 BaseT, WiFi
Power	DC 12 V / 1000 mA max. / IEEE802.3af PoE
Degree of protection	IP65
Material	Plastic
Temp. operation	-40° C ~ +53° C
Dimensions	138 (H) x 65 (W) x 27 (D) mm
Weight	400 g

Monitor

Brand	Safire
Model	SF-VIDISP01-7WIP
LCD	7" 1024x600, Capacitive
Operation mode	Tactile Buttons
Inputs	8 Configurable alarm entries
Audio	Two-way audio with microphone and speaker with noise reduction
Remote access	Mobile app or Safire Control Center-software
Memory	Slot MicroSD up to 32GB
Network interface	Ethernet 10/100 BaseT / RS485 / RTSP / WiFi 802.11b/g/n
Power	DC 12 V / 1000 mA max. / standard PoE (IEEE802.3af)
Temp. operation	-10° C ~ +55° C
Dimensions	200 (H) x 140 (W) x 15.1 (D) mm
Weight	750 g