

Networking / Switches / Unmanaged

SF-SW2016HIPOE-GF-240

SAFIRE



Features

- Desktop Switch
- 14 PoE+ ports 30W RJ45 10/100/1000 Mbps
- 2 Hi-portsPoE+ ports 60W 802.3bt 10/100/1000Mbps + 2 Uplink SFP 10/100/1000Mbps + 2 Uplink RJ45 10/100/1000Mbps
- AI Watchdog
- Supports PoE power supply up to 240W in total for all ports

Specifications

Interface	16 PoE ports + 2 Uplink RJ45 + 2 SFP Uplink
Port speed RJ45	18x 10/100/1000Mbps + 2x 10/100/1000Mbps
PoE features	Up to 240W in total for all ports Ports 1~14 PoE+ Up to 30W 802.3af/at Port 15~16 Hi-PoE Up to 60W 802.3af/at/bt
Transmission distance	130 meters
Bandwidth	40Gbps
MAC Table	8K
Latency	10 to 100MBps < 16?s (using 64 packet size byte)
AI PoE	PoE Watchdog Ports 1~16 - Automatic restart of the power supply to a PoE port when a possible failure is detected.
Power	Front Take 90~240V
Protections	6KV against Rays 8KV ESD Protection
Operating temperature	-30° C - 60° C
Dimensions	18 (D) x 45 (H) x 430 (W) mm
Weight	2,65Kg