

SF-IPCU014A-4B1W-PIR

SAFIRE SMART



Features

- Safire Smart
- Range B1 WiFi Camera IP cube WiFi
- 1/3" Progressive Scan CMOS
- 4 Megapixel (2560x1440)
- 2.1 mm Lens
- 0 Lux
- IR range 10 m
- Compression H.265+ / H.264+
- WDR
- MicroSD card
- Human detection
- Detector PIR
- Microphone and speaker
- Two-way audio
- Alarm input and output
- WEB interface, CMC, Smartphone and NVR
- ONVIF Compatible
- WiFi IEEE802.11b/g/n
- PoE (IEEE802.3af)
- P2P

Specifications

Brand	Safire Smart
Range	B1 WiFi
Image sensor	1/3" Progressive Scan CMOS
Maximum resolution	4 Megapixel (2560x1440)
Minimum resolution	Color: 0.035 Lux @(F1.2, AGC ON), 0 Lux con IR
IR range	10 m
Day/night	Removable ICR mechanical filter
Electronic Shutter	1/2~1/100.000 s
Main Stream rate	25 FPS (4Mpx, 3Mpx, 1080P, 720P)
Extra Stream rate	25 FPS (720P, D1, CIF)
Compression	H.265+ / H.264+ / H.265 / H.264
Bitrate	64 Kbps ~ 6 Mbps
Lens	2.1 mm
Field of View (FOV)	H: 94°, V: 50°, D: 115°
Range performance (DORI)	62 m (D), 25 m (O), 12 m (R), 6 m (I)
Image improvements	WDR (78dB), BLC, HLC, 3D-DNR, AWB, ROI, Función espejo, Máscara de privacidad, ROI
Motion Detection	Yes
Detector PIR	Detection up to 5m, 100°
Smart Functions	Human Detection
Smart Features	Motion detection, human detection, alarm input, PIR, memory card full, memory card failure, IP conflict or cable disconnected
Audio	1 Microphone / 1 Speaker Two-way audio with mobile app or web interface Recording messages for alarm
Audio Compression	G711A / U
Alarms	1 input / 1 relay
Network interface	Ethernet 10 / 100M BaseT

Internal memory	MicroSD card up to 128GB
Remote access	Web Browser, Safire Smart Smartphone App, Safire Smart VMS PC Software
P2P	Yes Sending push notifications in the event of a video exception, human detection, PIR detection or alarm input in the Safire Smart app
WiFi	2.4GHz IEEE802.11 b/g/n Up to 50m in open field
Interoperability	ONVIF
Power	DC 12 V / 666 mA / 5 W max. / PoE IEEE802.3af
Material	Metal and plastic
Field Of View (FOV)	Horizontal: 0°-230°; Vertical: 0°-71°; Rotation: 0°-360°
Temp. operation	-20° C ~ +50° C
Dimensions	130 (Al) x 71.7 (An) x 71.7(Fo) mm
Weight	140 g
Installation	Integrated table, ceiling or wall mount