

SF-VI134-IPW-FACIAL

SAFIRE SMART



Features

- Safire Smart
- IP video door entry system with 2 Mpx camera for 1 apartment
- Wide angle lens
- Built-in speaker and microphone
- IR night vision
- TCP/IP and WiFi connection
- PoE IEEE802.3af
- EM/MF card reader
- Opening by facial recognition and PIN code
- Remote door opening
- 2 door relay outputs
- Wiegand port and RS485
- MicroSD slot
- 3.5" full-color TFT display
- Complete configuration via web browser
- Remote monitoring via Safire Smart mobile app or indoor monitor software
- Push notifications through Safire Smart app
- ONVIF protocol for integration with video surveillance recorders
- Surface mounting
- Suitable for exterior IP67



- Anti-vandal IK04

Specifications

Brand	Safire Smart
Model	SF-VI134-IPW-FACIAL
Operating system	Linux
Image sensor	1/2.8" 2 Mpx Progressive Scan CMOS wide-angle IR
Camera resolution	1080p (1920x1080), 720p (1280x720), D1, CIF, 480x240
Image Functions	BLC / HLC / WDR / 3D DNR
Viewing angle	H: 139°, V: 74°, D: 170°
Audio	Bidirectional audio with microphone and speaker
Access control	Door opening with facial recognition, EM 125 kHz and MF 13.56 MHz and PIN cards Up to 10.000 cards and 10.000 faces
Keypad	Mechanical numeric call button panel with LED illumination
Screen	3.5" TFT LCD full color
Outputs	2 x lock relay, 1 x alarm output, 1 x RS485, 1 [%VAR%] x Wiegand OUT
Inputs	2 x exit button, 2 x door sensor, 2 x alarm input, 1 x Wiegand IN, 1 x tamper
Storage	MicroSD card (up to 256 GB)
Remote access	Web browser Safire Smart mobile application
Network interface	Ethernet 10/100 BaseT / WiFi / ONVIF
Power	DC 12 V / 1 A max. / IEEE802.3af PoE
Degree of protection	Suitable for exterior IP67 Anti-vandal IK04
Material	Plastic
Temp. operation	-20 °C ~ +60 °C
Dimensions	210 (H) x 104 (W) x 30 (D) mm
Weight	600 g