

Video-intercoms / Safire Smart / Panels

# SF-VI131-IPW-MF

SAFIRE SMART



## Features

---

- Safire Smart
- IP video door entry system with 2 Mpx camera for 1 apartment
- Wide angle lens
- Built-in speaker and microphone
- Night vision with LED illumination
- TCP/IP and WiFi connection
- PoE IEEE802.3af
- MF Card Reader
- Remote door opening
- 1 door relay output
- Port Wiegand
- MicroSD slot
- Complete configuration via web browser
- Remote monitoring via Safire Smart mobile app or indoor monitor software
- Push notifications through Safire Smart app
- ONVIF protocol for integration with video surveillance recorders
- Call status LED
- Surface mounting
- Suitable for exterior IP65

## Specifications

---

<b>Brand</b>	Safire Smart
<b>Model</b>	SF-VI131-IPW-MF
<b>Operating system</b>	Linux
<b>Image sensor</b>	1/2.8" 2 Mpx Progressive Scan wide-angle CMOS
<b>Camera resolution</b>	1080p (1920×1080), 720p (1280×720), D1, CIF
<b>Image Functions</b>	BLC / HLC / WDR / 3D DNR
<b>Viewing angle</b>	H: 139°, V: 74°, D: 170°
<b>Audio</b>	Bidirectional audio with microphone and speaker
<b>Access control</b>	Door opening with MF card 13.56 MHz Up to 3.000 cards
<b>Keypad</b>	Mechanical call button
<b>Outputs</b>	1 x lock relay, 1 x alarm output, 1 x RS485, 1 [%VAR%] x Wiegand OUT
<b>Inputs</b>	1 x exit button, 1 x door sensor, 1 x Wiegand IN, 1 x tamper
<b>Storage</b>	MicroSD card (up to 256 GB)
<b>Remote access</b>	Web browser Safire Smart mobile application
<b>Network interface</b>	Ethernet 10/100 BaseT / WiFi / ONVIF
<b>Power</b>	DC 12 V / 500 mA máx. / IEEE802.3af PoE
<b>Degree of protection</b>	Suitable for exterior IP65
<b>Material</b>	Plastic
<b>Temp. operation</b>	-20 °C ~ +50 °C
<b>Dimensions</b>	150 (H) x 50 (W) x 30 (D) mm
<b>Weight</b>	145 g