

IP CCTV / Professional IP cameras / Safire Smart / Bullet Cameras

SF-IPB380A-6E1-DL-0360

SAFIRE SMART



Features

- Safire Smart
- Range E1 with Artificial Intelligence
- Bullet IP camera
- 1/2.5" Progressive Scan CMOS
- 6 Megapixel (3200x1800)
- 3.6 mm Lens
- 0 Lux
- Dual Light scope 50 m
- Compression H.265+ / H.265 / H.264+ / H.264
- WDR
- Weatherproof IP67
- 3DNR
- Audio IN
- Integrated microphone
- MicroSD card
- Artificial intelligence: Classification of human and vehicle
- WEB, CMS, Smartphone and NVR interface
- ONVIF Compatible
- PoE (IEEE802.3af)

Specifications

Brand	Safire Smart
Range	E1
Image sensor	1/2.5" Progressive Scan CMOS
Maximum resolution	6 Megapixel (3200x1800)
Minimum illumination	Colour: 0.008 Lux @(F1.6, AGC ON), 0 Lux with IR
Dual Light Scope	IR: 50 m White Light: 40 m
Day/Night	Removable mechanical ICR filter
Electronic Shutter	1/2~1/100.000 s
Main Stream rate	20 FPS (6Mpx) 30 FPS (4Mpx, 1080P)
Extra Stream rate	25 FPS (720P, D1, CIF)
Third Stream Rate	25 FPS (D1, 480x240, CIF)
Compression	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Bitrate	64 Kbps ~ 8 Mbps
Lens	3.6 mm
Field Of View (FOV)	H: 78°, V: 38°, D: 94°
Range performance	105 m (D), 42 m (O), 21 m (R), 10 m (I)
Image improvements	WDR, BLC, HLC, 3D-DNR, AWB, ROI, Mirror Function, Privacy Mask, ROI
Motion Detection	Yes
Smart Features	Artificial intelligence based on human-vehicle classification on: Area Intrusion, Line Crossing, Entry Region, Exit Region Other smart events: dropped object, removed object, Video exceptions (change of scene, video loss, ...)
Audio	1 Input / Built-in microphone
Audio Compression	G711A / U
Network interface	Ethernet 10 / 100M BaseT
Internal memory	MicroSD card up to 256GB

Remote access	Web Browser, Smartphone App Safire Smart, PC Software Safire Smart VMS
Interoperability	ONVIF
Power	DC 12 V / 9.5 W max. / IEEE802.3af PoE
Degree of protection	Weatherproof IP67
Material	Metal and plastic
Temp. operation	-30° C ~ +60° C
Dimensions	80.5 (H) x 80.5 (W) x 217.8 (D) mm
Weight	680 g