

SF-IPB580ZA-4E1-DL

Safire Smart

Bullet IP Camera range E1 Artificial Intelligence

Resolution 4 Megapixel (2560x1440)

Motorized Lens 2.8-12 mm | Audio IN

| DL 50m

AI: Classification of human and vehicle

IP67 Waterproof | PoE (IEEE802.3af)

| P2P



Safire Smart

Range E1 with Artificial Intelligence

Bullet IP camera

1/3" Progressive Scan CMOS

4 Megapixel (2560x1440)

2.8-12mm motorised lens

0 Lux -Dual Light Range 50 m

Compression H.265+ / H.265 / H.264+ / H.264

WDR

3DNR

Audio IN

Integrated microphone

MicroSD card

Artificial intelligence: Classification of human and vehicle

WEB, CMS, Smartphone and NVR interface

ONVIF Compatible

P2P

PoE (IEEE802.3af)

Weatherproof IP67

Specifications

Brand	Safire Smart
Range	E1
Image sensor	1/3" Progressive Scan CMOS
Maximum resolution	4 Megapixel (2560x1440)
Minimum illumination	Colour: 0.005 Lux @(F1.6, AGC ON), 0 Lux with IR
Dual Light Scope	IR: 50 m White Light: 40 m
Day/Night	Removable mechanical ICR filter
Electronic Shutter	1/2~1/100.000 s
Main Stream rate	30 FPS (4MP, 3MP, 1080P, 720P)
Extra Stream rate	30 FPS (720P, D1, VGA, CIF)
Third Stream Rate	30 FPS (D1, 480x240, CIF)
Compression	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Bitrate	64 Kbps – 6 Mbps
Lens	Motorised 2.8-12mm
Field Of View (FOV)	H: 92°~31°, V: 48°~17.2°, D: 112°~35.6°
Range performance	189~64 m (D), 75~26 m (O), 38~13 m (R), 19~6 m (I)
Image improvements	WDR, BLC, HLC, 3D-DNR, AWB, ROI, Mirror Function, Privacy Mask, ROI
Motion Detection	Yes
Smart Features	Artificial intelligence based on human-vehicle classification on: Area Intrusion, Line Crossing, Entry Region, Exit Region Other smart events: dropped object, removed object, Video exceptions (change of scene, video loss, ...)
Audio	1 Input / Built-in microphone
Audio Compression	G711A / U
Network interface	Ethernet 10 / 100M BaseT
Internal memory	MicroSD card up to 256GB
Remote access	Web Browser, Smartphone App Safire Smart, PC Software Safire Smart VMS
Interoperability	ONVIF
P2P	Yes
Power	DC 12 V / 8.5 W max. / IEEE802.3af PoE
Degree of protection	Weatherproof IP67
Material	Metal and plastic
Temp. operation	-30° C ~ +60° C
Dimensions	80.5 (H) x 80.5 (W) x 217.8 (D) mm
Weight	680 g