

IP CCTV / Professional IP cameras / Safire Smart / Dome Cameras

SF-IPD040-4B1

SAFIRE SMART



Features

- Safire Smart
- Economic B1 range
- IP Dome Camera
- 1/3" Progressive Scan CMOS
- 4 Megapixel (2560x1440)
- 2.8 mm Lens
- 0 Lux
- IR Range 30 m
- Compression H.265 / H.264
- Anti-vandal IK10
- 3DNR
- Artificial intelligence: Classification of human and vehicle
- WEB, CMS, Smartphone and NVR interface
- ONVIF Compatible
- PoE (IEEE802.3af)
- 3 axis
- Weatherproof IP67

Specifications

| | |
|------------------------------|---|
| Brand | Safire Smart |
| Range | B1 economic |
| Image sensor | 1/3" Progressive Scan CMOS |
| Maximum resolution | 4 Megapixel (2560x1440) |
| Minimum illumination | Colour: 0.03 Lux @(F1.6, AGC ON), 0 Lux with IR |
| IR range | 30 m |
| Day/Night | Removable mechanical ICR filter |
| Electronic Shutter | 1/2~1/100.000 s |
| Main Stream rate | 25 FPS (4Mpx, 3Mpx, 1080P, 720P) |
| Extra Stream rate | 25 FPS (720P, D1, CIF) |
| Third Stream Rate | 25 FPS (D1, 480x240, CIF) |
| Compression | H.265 / H.264 |
| Bitrate | 64 Kbps ~ 8 Mbps |
| Lens | 2.8 mm |
| Field Of View (FOV) | H: 98°, V: 53°, D: 116° |
| Range performance | 61 m (D), 24 m (O), 12 m (R), 6 m (I) |
| Image improvements | WDR, BLC, HLC, 3D-DNR, AWB, ROI, Mirror Function, Privacy Mask, ROI |
| Motion Detection | Yes |
| Intelligent functions | VCA Rules: Area intrusion, line crossing, abandoned object, removed object, video exception (change of scene) |
| Audio | No |
| Audio Compression | G711A / U |
| Network interface | Ethernet 10 / 100M BaseT |
| Internal memory | No |
| Remote access | Web Browser, Smartphone App Safire Smart, PC Software Safire Smart VMS |

| | |
|-----------------------------|---|
| Interoperability | ONVIF |
| 3 Axis | Yes |
| Power | DC 12 V / 375 mA / < 4 W máx. / IEEE802.3af PoE |
| Degree of protection | Waterproof IP67, Anti-vandal IK10 |
| Material | Metal and plastic |
| Temp. operation | -30° C ~ +60° C |
| Dimensions | 110 (Ø) × 83.3 (H) mm |
| Weight | 500 g |