

SF-IPD360A-6I1

SAFIRE SMART



Features

- Safire Smart
- Range I1 fisheye
- Fisheye IP Dome Camera
- 1/2.9" Progressive Scan CMOS
- 6 Megapixel (2160x2160)
- 1.1 mm Lens
- Wide-angle 360°
- 0 Lux
- IR Range 30 m
- Compression H.265 / H.264
- WDR
- 3DNR
- Integrated microphone
- Audio
- Alarms
- MicroSD card up to 256GB
- WEB, CMS, Smartphone and NVR interface
- ONVIF Compatible
- PoE (IEEE802.3af)
- Weatherproof IP67

Specifications

Brand	Safire Smart
Range	I1
Image sensor	1/2.9" Progressive Scan CMOS
Maximum resolution	6 Megapixel (2160x2160)
Minimum illumination	Colour: 0.068 Lux @(F2.0, AGC ON), 0 Lux with IR
IR range	30 m
Day/Night	Removable mechanical ICR filter
Electronic Shutter	1/2~1/100.000 s
Resolution	- Fisheye + panorama + 3 PTZ 25fps@(2160x2160 / 1920x1920 / 1440x1440 / 960x960 / 480x480) 3x 15fps@(1920x1080 / 704x576), 15fps@(960x540 / 480x240) - Fisheye + 4 PTZ 50Hz: 25fps@(2160x2160 / 1920x1920 / 1440x1440 / 960x960 / 480x480) 4x 15fps@(960x 540 / 480x240)
Compression	H.265 / H.264 / MJPEG
Bitrate	64 Kbps ~ 8 Mbps
Lens	1.1 mm (360°)
Installation	Ceiling or Wall
Image improvements	WDR, BLC, HLC, 3D-DNR, AWB, ROI, Mirror Function, Privacy Mask, ROI
Motion Detection	Yes
Audio	Integrated microphone, 1 input and 1 output
Audio Compression	G711A / U
Alarms	1 Input / 1 Relay
Video output	1 BNC CVBS output
Network interface	Ethernet 10 / 100M BaseT
Internal memory	MicroSD card up to 256GB
Remote access	Web Browser, Smartphone App Safire Smart, PC Software Safire Smart VMS

Interoperability	ONVIF
Power	DC 12 V / 950 mA / 10.5 W max. / IEEE802.3af PoE
Degree of protection	Weatherproof IP67
Material	Metallic
Temp. operation	-30° C ~ +60° C
Dimensions	130 (?) x 41 (Fo) mm
Weight	650 g