

IP CCTV / Professional IP cameras / Safire Smart / Turret cameras

SF-IPT520ZA-4E1-GREY

SAFIRE SMART



Features

- Safire Smart
- E1
- Turret IP Camera
- 1/3" Progressive Scan CMOS
- 4 Megapixel (2560x1440)
- 2.8~12mm Motorised Lens
- 0 Lux
- IR Range 50 m
- Compression H.265 / H.264
- WDR
- Grey
- 3DNR
- Integrated microphone
- Audio
- Artificial intelligence: Classification of human and vehicle
- WEB, CMS, Smartphone and NVR interface
- ONVIF Compatible
- PoE (IEEE802.3af)
- Weatherproof IP67

Specifications

Brand	Safire Smart
Range	E1
Image sensor	1/3" Progressive Scan CMOS
Maximum resolution	4 Megapixel (2560x1440)
Minimum illumination	Colour: 0.005 Lux @(F1.6, AGC ON), 0 Lux with IR
IR range	50 m
Day/Night	Removable mechanical ICR filter
Electronic Shutter	1/2~1/100.000 s
Main Stream rate	25 FPS (4Mpx, 3Mpx, 1080P, 720P)
Extra Stream rate	25 FPS (720P, D1, CIF)
Third Stream Rate	25 FPS (D1, 480x240, CIF)
Compression	H.265 / H.264
Bitrate	64 Kbps ~ 8 Mbps
Lens	Motorised 2.8~12 mm
Viewing Angle (FOV)	H: 92-31°, V: 48-17.2°, D: 112-35.6°
Range performance	W: 64 m (D), 25 m (O), 13 m (R), 6 m (I) T: 188 m (D), 75 m (O), 38 m (R), 19 m (I)
Image improvements	WDR, BLC, HLC, 3D-DNR, AWB, ROI, Mirror Function, Privacy Mask, ROI
Motion Detection	Yes
Smart Features	Artificial Intelligence based classification of human and vehicle on: Area Intrusion, Line Crossing, Entry Region, Exit Region Other smart events: dropped object, removed object, Video exceptions (change of scene, video loss, ...)
Audio	Built-in microphone, 1 Input
Audio Compression	G711A / U
Network interface	Ethernet 10 / 100M BaseT
Internal memory	MicroSD card up to 256GB

Remote access	Web Browser, Smartphone App Safire Smart, PC Software Safire Smart VMS
Interoperability	ONVIF
Power	DC 12 V / 666 mA / 8 W max. / IEEE802.3af PoE
Degree of protection	Weatherproof IP67
Material	Metallic
Temp. operation	-30° C ~ +60° C
Dimensions	111.5 (Ø) x 99.6 (h) mm
Weight	650 g