

IP CCTV / Professional NVRs / Safire Smart

SF-NVR6108-8P-B2

SAFIRE SMART



Features

- Safire Smart
- B2
- NVR for IP cameras
- 8 CH
- 8 PoE ports
- 80 Mbps bandwidth supported
- Maximum resolution 8 Megapixel (3840x2160)
- Compression H.265+/H.265/H.264+/H.264
- Outputs 4K HDMI & VGA
- POS Function
- ONVIF Compatible
- Face detection
- Intelligent searches
- IP Dual Stream Access
- Mouse
- RCA Audio
- Camera Alarms
- Space for 1 HDD
- WEB, CMS and Smartphone interface

Specifications

Brand	Safire Smart
Range	B2
Inputs for IP cameras	8CH IP
PoE inputs	8CH
IP compatible cameras	Safire Smart (native protocol), ONVIF
Video outputs	1 HDMI 4K, 1 VGA
Main Stream recording	8MP/6MP/5MP/4MP/3MP/1080P/1280×1024/960P/720P/960H/D1/CIF
Decoding capacity	1CH: 8Mpx 6CH: 1080P
Video compression format	H.265+ / H.265 / H.264+ / H.264
Audio Compression	G.711(U/A)
Total bandwidth	80 Mbps downstream / 80 Mbps upstream
Display resolution	HDMI: 3840x2160@60FPS/30FPS, 2560x1440, 1920x1080, 1280x1024, 1280x720, 1024x768 VGA: 1920x1080, 1280x1024, 1024x768
Audio	1 RCA input / 1 RCA output / 8 Channels per camera
Alarms	Camera alarms are available
POS Function	Yes
Intelligent functions	Face detection up to 8CH per camera Face detection up to 2CH per NVR Image searches via recorder, APP and software Statistical information on face results. Smart event searches by human and vehicle in 8CH per camera Intelligent event searches by human and vehicle in 2CH per NVR Metadata extraction per camera License plate recognition by camera
Dewarping	Fisheye camera dewarping available
Recording method	Manual, programmed, motion detection, smart events, alarm input, POS
Simultaneous multifunction	Pentaplex: Live, Recording, Playback, Backup and Remote Access



External Backup	USB memory stick / USB HDD / USB CD-RW / USB DVR-RW /
Internal memory	1x 3.5" HDD SATA3.0 up to 10 TB (not included)
Communication	2 x USB 2.0 / 1 x RJ45 10/100/1000M (Ethernet) / RS485
Remote access	Web Browser, Safire Smartphone App and PC Software Safire Smart VMS
Power	DC 48V / 1.8A (No hard disk)
Operating temperature	-10°C ~50°C, Humidity 10~90%
Dimensions / Weight	45(H) x 300(W) x 249(D)mm / 1Kg