

IP CCTV / Professional NVRs / Safire Smart

SF-NVR6108-B2

SAFIRE SMART



Features

- Safire Smart
- B2
- NVR for IP cameras
- 8 CH
- 80 Mbps bandwidth supported
- Maximum resolution 8 Megapixel (3840x2160)
- Compression H.265+/H.265/H.264+/H.264
- Outputs 4K HDMI & VGA
- POS Function
- ONVIF Compatible
- Face detection
- IP Dual Stream Access
- Mouse
- RCA Audio
- Camera Alarms
- Space for 1 HDD
- WEB, CMS and Smartphone interface

Specifications

Brand	Safire Smart
Range	B2 NVR series
Inputs for IP cameras	8CH IP
IP compatible cameras	Safire Smart (native protocol), ONVIF
Bidirectional audio	1 input / 1 RCA output
Video outputs	1 HDMI 4K, 1 VGA
Main Stream recording	8MP/6MP/5MP/4MP/3MP/1080P/1280x1024/960P/720P/ 960H/D1/CIF
Decoding capacity	1CH 8Mpx 6CH 1080P
Video compression format	H.265+ / H.265 / H.264+ / H.264
Audio Compression	G.711(U/A)
Total bandwidth	80 Mbps downstream / 80 Mbps upstream
Display resolution	HDMI: 3840x2160@60FPS/30FPS, 2560x1440, 1920x1080, 1280x1024, 1280x720, 1024x768 VGA: 1920x1080, 1280x1024, 1024x768
Audio	Two-way RCA Audio / Provides audio through camera
Alarms	Camera alarms are available
POS Function	Yes
Intelligent functions	Face detection up to 8CH per camera Face detection up to 2CH per NVR Image searches via recorder, APP and software Statistical information on face results. Smart event searches by human and vehicle in 8CH per camera Intelligent event searches by human and vehicle in 2CH per NVR Metadata extraction per camera
Recording method	Manual, programmed, motion detection, smart events, alarm input, POS
Simultaneous multifunction	Pentaplex: Live, Recording, Playback, Backup and Remote Access
External Backup	USB memory stick / USB HDD / USB CD-RW / USB DVR-RW /
Internal memory	1x 3.5" HDD SATA3.0 up to 10 TB (not included)

Communication	2 x USB 2.0 / 1 x RJ45 10/100/1000M (Ethernet) / RS485
Remote access	Web Browser, Safire Smartphone App and PC Software Safire Smart VMS
Power	DC 12V / 1.5A (No hard disk)
Operating temperature	-10°C ~50°C, Humidity 10~90%
Dimensions / Weight	45(H) x 300(W) x 249(D)mm / 1Kg